



Reliable deployment, efficient drill-up and 100% zonal isolation in ONE package. Introducing Lonestar Completion Tools ONEplug™, the first and only composite frac plug manufactured from ONE continuous piece of material.

Features

The ONEplug's™ innovative design incorporates all the features of a standard plug into a plug with a single piece construction. This design helps mitigate issues with manufacturing and assembly as well as unforeseen presetting events. All of this is accomplished by eliminating loose components like slips, elements, cones and backup devices. Additional benefits of the single piece construction include increased pump down capability and reduced overall material volume. The ONEplug™ also incorporates an expandable non-elastomeric seal that provides 100% sealing for complete zonal isolation and casing protection. Optional features include wireline adapter kits for all setting tool styles, dissolvable expandable seals and ball-on-seat configuration.

ONEplug™ Specifications

Casing Size	Weight Range	Ball Size	O.D.	Length	Pressure	Temp (F)	Ball Drop	Ball-in-Place
4.500"	11.6#-15.1#	2.000"	3.550"	14.100"	10,000	325	✓	✓
5.000"	18.0#-21.4#	2.250"	3.875"	14.285"	10,000	325	✓	✓
5.500"	17.0#-23.0#	2.500"	4.440"	15.100"	10,000	325	✓	✓
5.500"	23.0#-26.0#	2.500"	4.280"	15.500"	10,000	325	✓	✓
6.000"	23.0#-30.0#	2.500"	4.750"	16.230"	10,000	325	✓	✓

ONEplug™

Zonal Isolation Device